

TYPE	TECHNICAL SPECIFICATIONS					ACCESSORIES	
	Case code	Power (W)	P.F.C.	Without protection (type A)	With protection (type B)	Dimmable with phase control	Remote dimmer 1-10 Vdc
20 mA							
<i>New</i> 4000V 20mA	3	50			√	√	
40 mA							
990V 40mA	1	15		√			
<i>New</i> 2000V 40mA	3	40			√	√	
<i>New</i> 2000V 40mA	3	45	√		√		√
<i>New</i> TWIN 2x990V 40mA	6	50			√	√	
50 mA							
<i>New</i> 6500V 50mA	4	120	√		√		√
60 mA							
990V 60mA	2	20		√	√		
<i>New</i> TWIN 2x990V 60mA	6	65			√	√	
<i>New</i> TWIN 2x990V 60mA	6	70	√		√		√
80 mA							
990V 80mA	2	20		√	√		
<i>New</i> 990V 80mA	3	50			√	√	
<i>New</i> 990V 80mA	3	40	√		√		√
100 mA							
<i>New</i> 990V 100mA	3	50		√	√	√	
<i>New</i> 990V 100mA	3	50	√		√		√
<i>New</i> 2000V 100mA	3	90	√		√		√
<i>New</i> 2500V 100mA	4	120	√		√		√
<i>New</i> TWIN 2x990V 100mA	6	80			√	√	
<i>New</i> TWIN 2x990V 100mA	6	90	√		√		√
180 mA							
<i>New</i> 900V 180mA	3	90			√	√	
<i>New</i> 900V 180mA	3	85	√		√		√
<i>New</i> 2100V 180mA	5	130	√		√		√

Case code	L Length mm	W Widht mm	H Height mm	Weight kg
1	106	33	32	0,3
2	114	44	35	0,4
3	150	48	35	0,6
4	163	59	46	1,1
5	184	60	46	1,2
6	262	60	38	1,2